

# Triggering Conditions and Data Quality Stationary Vehicle Warning

**CAR 2 CAR Communication Consortium** 



#### **About the C2C-CC**

Enhancing road safety and traffic efficiency by means of Cooperative Intelligent Transport Systems and Services (C-ITS) is the dedicated goal of the CAR 2 CAR Communication Consortium. The industrial driven, non-commercial association was founded in 2002 by vehicle manufacturers affiliated with the idea of cooperative road traffic based on Vehicle-to-Vehicle Communications (V2V) and supported by Vehicle-to-Infrastructure Communications (V2I). The Consortium members represent worldwide major vehicle manufactures, equipment suppliers and research organisations.

Over the years, the CAR 2 CAR Communication Consortium has evolved to be one of the key players in preparing the initial deployment of C-ITS in Europe and the subsequent innovation phases. CAR 2 CAR members focus on wireless V2V communication applications based on ITS-G5 and concentrate all efforts on creating standards to ensure the interoperability of cooperative systems, spanning all vehicle classes across borders and brands. As a key contributor, the CAR 2 CAR Communication Consortium and its members work in close cooperation with the European and international standardisation organisations.

#### **Disclaimer**

The present document has been developed within the CAR 2 CAR Communication Consortium and might be further elaborated within the CAR 2 CAR Communication Consortium. The CAR 2 CAR Communication Consortium and its members accept no liability for any use of this document and other documents from the CAR 2 CAR Communication Consortium for implementation. CAR 2 CAR Communication Consortium documents should be obtained directly from the CAR 2 CAR Communication Consortium.

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media. © 2021, CAR 2 CAR Communication Consortium.



## **Document information**

Number:	2006	Version:	n.a.	Date:	2021-12-17
Title:	Triggering Col Vehicle Warnin	nditions and Data C	uality Stationary	Document Type:	RS
Release	1.6.1				
Release Status:	Public				
Status:	Final				

**Table 1: Document information** 



# **Changes since last version**

Title:	Triggering Conditions and Data Quality Stationary Vehicle Warning			
Date	Changes	Edited by	Approved	
2021-12-17	<ul> <li>Added marking of requirements, indicating relevance for interoperability according to [CPOC]</li> <li>Minor corrections</li> </ul>	_	Steering Committee	
2021-07-23	Consideration of PTW aspects in the requirements	Release Management	Steering Committee	
2021-03-12	No changes	Release Management	Steering Committee	
2020-12-16	Minor editorial changes	Release Management	Steering Committee	
2020-07-31	Minor corrections	Release Management	Steering Committee	
2020-03-27	Minor corrections	Release Management	Steering Committee	
2019-09-13	Minor corrections	Release Management	Steering Committee	
2018-08-31	Minor corrections	Release Management	Steering Committee	

**Table 2: Changes since last version** 



## **Table of contents**

About the C2	2C-CC	1
Disclaimer		1
Document in	formation	2
Changes sin	ce last version	3
Table of cont	ents	4
List of tables		5
	tion	
	ns	
	ment specifications	
	tionary vehicle warning - stopped vehicle	
3.1.1	Description of vehicle C-ITS service	8
3.1.2	Triggering conditions	
3.1.3	Termination conditions	
3.1.4	Update	
3.1.5	Repetition duration and repetition interval	
3.1.6	Traffic class	
3.1.7	Message parameters	
3.1.8	Network and transport layer	14
3.1.9	Security layer	15
3.2 Stat	tionary vehicle warning - broken-down vehicle	15
3.2.1	Description of vehicle C-ITS service	15
3.2.2	Triggering conditions	
3.2.3	Termination conditions	17
3.2.4	Update	18
3.2.5	Repetition duration and repetition interval	19
3.2.6	Traffic class	19
3.2.7	Message parameters	
3.2.8	Network and transport layer	22
3.2.9	Security layer	
3.3 Stat	iionary vehicle warning - post-crash	22
3.3.1	Description of vehicle C-ITS service	22
3.3.2	Triggering conditions	23
3.3.3	Termination conditions	24
3.3.4	Update	
3.3.5	Repetition duration and repetition interval	
3.3.6	Traffic class	
3.3.7	Message parameters	
3.3.8	Network and transport layer	
3.3.9	Security layer	29



# **List of tables**

Table 1: Document information	2
Table 2: Changes since last version	3
Table 3: Information quality of 'stationary vehicle — stopped vehicle'	10
Table 4: DENM data elements of 'stationary vehicle warning — stopped vehicle'	12
Table 5: Information quality of 'stationary vehicle - broken-down vehicle'	17
Table 6: DENM data elements of 'stationary vehicle warning — broken-down vehicle'	19
Table 7: Information quality of 'stationary vehicle — post-crash'	24
Table 8: DENM data elements of 'stationary vehicle warning — post-crash'	26



#### 1 Introduction

#### Other (informational)

RS\_tcStVe\_183

This document describes the triggering conditions for stationary vehicle warning for the following three vehicle C-ITS service:

- 'stationary vehicle warning stopped vehicle';
- 'stationary vehicle warning broken-down vehicle';
- 'stationary vehicle warning post-crash'.



## 2 Definitions

Definition RS\_tcStVe\_642

'Vehicle speed' is the length of the velocity-vector of the reference position point.



## 3 Requirement specifications

## Requirement (i) RS\_tcStVe\_208

The Stationary Vehicle Warning vehicle C-ITS services deals with vehicles which are 'stationary'. A stationary vehicle is defined in RS BSP 511.

Tested by:

## 3.1 Stationary vehicle warning - stopped vehicle

#### 3.1.1 Description of vehicle C-ITS service

#### Other (informational)

RS tcStVe 184

This clause describes the triggering of V2V messages for stopped vehicles. Various reasons could lead to a situation involving a stopped vehicle, like human problems, accidents, rubbish collection, delivery service or a stopping bus. This clause focuses on situations without particular information about the reason of the stopping maneuver.

#### Other (informational)

RS\_tcStVe\_185

The following vehicle C-ITS services are related to this service, because they share similar triggering conditions:

- 'special vehicle warning stationary recovery service warning';
- 'stationary vehicle warning broken-down vehicle';
- 'stationary vehicle warning post-crash'.

Requirement (i) RS\_tcStVe\_116

A DENM signal for 'Stationary vehicle warning - stopped vehicle' C-ITS service shall be sent to the stack only if the conditions described in the clauses 3.1.2, 3.1.3 and 3.1.4 are evaluated as being met. If these conditions are not fulfilled, a DENM signal for this C-ITS service shall not be generated.

Note: A DENM signal prompts the stack to generate a new, update or cancellation DENM respectively.

Tested by:

## 3.1.2 Triggering conditions

#### 3.1.2.1 Preconditions

#### Requirement (i)

RS\_tcStVe\_117

The following preconditions shall be satisfied when this use case is triggered:

 no breakdown warning message, that prevents the driver from continuing to drive, e.g. oil pressure, engine temperature, engine malfunction warning light or other comparable warning messages.

Note: This service is not required to check ignition terminal 15 status for triggering (can be on or off). Operation of this service is optional when ignition terminal 15 is off.

Tested by:



Requirement (i) RS\_tcStVe\_205

Parallel activation with the other related vehicle C-ITS services shall be avoided. Where the 'broken-down vehicle' and/or 'post-crash' vehicle C-ITS services are triggered simultaneously, the vehicle C-ITS services shall be prioritised as follows:

- 1.) 'post-crash' (highest priority);
- 2.) 'broken-down vehicle';
- 3.) 'stopped vehicle' (lowest priority).

The higher priority service shall generate a new DENM and the overruled lower priority service shall not continue to generate update DENMs. An active repetition of the lower priority service may continue, a termination DENM for lower priority services should not be generated.

Tested by:

#### 3.1.2.2 Service-specific conditions

#### Requirement (i)

RS\_tcStVe\_118

If the preconditions in RS\_tcStVe\_117 and all of the following conditions are satisfied, the triggering conditions for this vehicle C-ITS service are fulfilled and the generation of a DENM shall be triggered:

- the ego vehicle has enabled hazard lights;
- the vehicle is stationary;
- the Triggering Timer has expired.

Note: PTWs may not be equipped with hazard lights. PTWs without hazard lights will not trigger this use case.

Tested by:

Requirement (i) RS\_tcStVe\_120

If the vehicle is stationary, the *Triggering Timer* shall be set to 30 s and shall be started counting down.

The *Triggering Timer* shall be further reduced by 10 s for each of the following conditions that is fulfilled:

- a) the automatic transmission (AUT) is set to 'park' for at least 3 s;
- b) the gear box is set to idle for at least 3 s;
- c) the parking brake is enabled for at least 3 s:
- d) an arbitrary number of the seatbelt buckles change from 'connected' to 'disconnected' for at least 3 s;

The *Triggering Timer* shall be set to 0 s if at least one of the following conditions is fulfilled:

- e.1) an arbitrary number of doors are open for at least 3 s OR
- e.2) e.2) cprw>the side or main stand is used for at least 3 s/prw>;
- f) the ignition terminal is switched from on to off for at least 3 s;
- g) the boot is open for at least 3 s;
- h) the bonnet is open for at least 3 s.

Tested by:

Requirement (i) RS\_tcStVe\_121



All above-listed procedures for the timer reduction shall be applied only once during initial detection. If the *Triggering Timer* has been counted down to 0, no further reduction is necessary in the current detection cycle.

Tested by:

Requirement (i) RS\_tcStVe\_122

During the runtime of the *Triggering Timer*, the vehicle shall be stationary. Otherwise, the detection shall be cancelled.

Tested by:

#### 3.1.2.3 Information quality

#### Requirement (i)

RS tcStVe 123

The value of the data element *informationQuality* in the DENM depends on the current conditions from a) to h) of the requirement RS\_tcStVe\_120. The *informationQuality* value shall be set in accordance with the following table (highest possible value shall be used):

Table 3: Information quality of 'stationary vehicle'

Event detection	Value of InformationQuality	
No TRCO-compliant implementation	unknown(0)	
None of the conditions a) — h) are fulfilled.	1	
At least one condition of a) — d) is fulfilled.	2	
At least one condition of e) — h) is fulfilled.	3	

Note: an update of the information quality is performed as described in RS\_tcStVe\_124.

Tested by:

#### 3.1.3 Termination conditions

#### Requirement (i)

RS tcStVe 125

This vehicle C-ITS service is terminated by a cancellation of the originating vehicle C-ITS station. At the termination of the vehicle C-ITS service, update DENM request shall be terminated.

Tested by:

#### 3.1.3.1 Cancellation

#### Requirement (i)

RS\_tcStVe\_126

If at least one of the following conditions is satisfied before the time period set in the data element *validityDuration* has expired, the generation of a cancellation DENM shall be triggered:

- a) the vehicle is no longer stationary for a duration of 5 s;
- b) the hazard lights are disabled;



c) the position of the vehicle has changed more than 500 m (e.g. because the vehicle has been towed away).

Note: The cancellation condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that cancellation condition.

Tested by:

#### 3.1.3.2 Negation

Requirement (i) RS\_tcStVe\_127

A negation DENM shall not be used for this vehicle C-ITS service.

Tested by:

## **3.1.4 Update**

Requirement (i) RS\_tcStVe\_128

If the previously detected *Stopped Vehicle* was not cancelled (see RS\_tcStVe\_126), the generation of an update DENM shall be triggered every 15 s.

Tested by:

Requirement (i) RS\_tcStVe\_129

In the update phase, only the triggering conditions shall be checked (further evaluation of timers shall not be executed).

Tested by:

Requirement (i) RS tcStVe 130

New values shall be assigned to data fields or elements in the DENM according to the changed event (e.g. detectionTime or informationQuality, see RS\_tcStVe\_133).

Note: The update condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that update condition.

Tested by:

Requirement (i) RS\_tcStVe\_124

If the triggering conditions change between two updates, the *informationQuality* shall not be changed until the next update. If the changed conditions are still fulfilled while the DENM is updated, the *informationQuality* shall be updated.

Tested by:

#### 3.1.5 Repetition duration and repetition interval

Requirement (i) RS\_tcStVe\_131

DENMs, that are new, have been updated or have been cancelled shall be repeated for a repetitionDuration of 15 s with a repetitionInterval of 1 s. Therefore, the interface parameters Repetition and Repetition interval between the application and the DEN basic service shall be set in accordance with the above values.



Note: The *validityDuration* is set to 30 s. Therefore, one can prevent a gap of DENMs if the *repetitionDuration* of the original DENM has expired and the update has not yet been received. Note: Where two DENMs with the same *causeCode* originate from the same vehicle C-ITS station, the case shall be managed by the receiving C-ITS station.

Tested by:

#### 3.1.6 Traffic class

Requirement (i) RS\_tcStVe\_132

New, update and cancellation DENMs shall be set to traffic class 1.

Tested by:

#### 3.1.7 Message parameters

#### 3.1.7.1 **DENM**

Requirement (i) RS\_tcStVe\_133

The following table specifies the data elements of the DENM that shall be set.

Table 4: DENM data elements of 'stationary vehicle warning — stopped vehicle'

Data field	Value					
	Management container					
actionID	Identifier of a DENM. Shall be set in accordance with [TS 102 894-2].					
detectionTime	Timestamplts-timestamp at which the event is detected by the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].					
	Shall be refre	shed for an update DEN	NM.			
referenceTime	TimestampIts-timestamp at which a new, update or cancell DENM is generated. Shall be set in accordance with [TS 102 2].					
termination	Shall not be set in the case of new or update DENM. Shall be set to isCancellation(0) in the case of a cancellation DENM.		•			
eventPosition	ReferencePosition. Shall be set in accordance with [TS 102 894-2].					
	Shall be refreshed for an update DENM.					
relevanceDistance	lessThan1000m(4)					
	If the roadTyp	oe is known, the value s	hall be set as follows:			
relevanceTrafficDirection	RoadType	Direction				
relevance HamicDirection	0	allTrafficDirections(0)				
	1	upstreamTraffic(1)				



	2	allTrafficDirections(0)			
	3	upstreamTraffic(1)			
	Otherwise, the value shall be set to allTrafficDirections(0)				
validityDuration	30 s				
stationType	The type of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].				
	Situation container				
informationQuality	See RS_tcSt	Ve_123. Shall be refresl	hed for every update DENM.		
causeCode	stationaryVel	nicle(94)			
subCauseCode	unavailable(0	)			
	Loc	cation container			
eventSpeed	Speed of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].				
	Shall be refre	shed for an update DEN	IM.		
eventPositionHeading	Heading of the originating vehicle C-ITS station. Shall be se accordance with [TS 102 894-2].				
	Shall be refreshed for an update DENM.				
	PathHistory of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].				
traces	If the PathDeltaTime is used in the PathPoints, the PathDeltaTime of the first PathPoint (closest point to the ReferencePosition) shall be refreshed for an update DENM. All other PathPoints shall not be refreshed. If the PathDeltaTime of the first PathPoint exceeds the maximum value in accordance with [TS 102 894-2], the PathDeltaTime shall not be further refreshed. If the PathDeltaTime is not used in the PathPoints, the PathHistory shall not be refreshed for an update DENM.				
	RoadType of the road on which the detecting vehicle C-ITS station is situated.				
	Shall be refreshed for an update DENM.				
	Shall be set in accordance with [TS 102 894-2] in combination with the following rules:				
roadType	Urban / non-Urban	Structural separation	Data element		
	Urban	No	urban- NoStructuralSeparation ToOppositeLanes(0)		
	Urban	Yes	urban- WithStructuralSeparation ToOppositeLanes(1)		



		<u>,                                      </u>	
Urban	Unknown	urban- NoStructuralSeparation ToOppositeLanes(0)	
Non-urban	No	nonUrban- NoStructuralSeparation ToOppositeLanes(2)	
Non-urban	Yes	nonUrban- WithStructuralSeparation ToOppositeLanes(3)	
Non-urban	Unknown	nonUrban- NoStructuralSeparation ToOppositeLanes(2)	
Ala	carte container		
If the lanePosition is provided by an on-board sensor (e.g. racamera), the value shall be set in accordance with [TS 102 89 Use of GNSS and a digital map to estimate the lane number is lanePosition legitimate for this version of the triggering condition.			
If the lanePosition is unknown, the data element shall be omitted.			
Shall be refre	eshed for an update DENM.		
Alacarte container: StationaryVehicleContainer			
Shall be set in accordance with the duration in minutes of detecting vehicle C-ITS station being stationary. Shall be saccordance with [TS 102 894-2].			
Shall be refreshed for an update DENM.			
	Non-urban  Non-urban  If the informate determined, the lanePostamera), the Use of GNSS legitimate for lifthe lanePost Shall be refrested to the lanePost arte containe  Shall be set detecting vehaccordance with the lane with the lanePost arte containe	Non-urban  Non-urban  Yes  Non-urban  Unknown  If the information about the urban/determined, the data element shall be alement, the value shall be set in account of the trigger of GNSS and a digital map to est legitimate for this version of the trigger of the lanePosition is unknown, the day and the lanePosition is unknown, the day and the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown, the day are container: StationaryVehicleComparts of the lanePosition is unknown.	

Tested by:

#### 3.1.7.2 CAM

#### Requirement (i)

RS\_tcStVe\_134

CAM adaption shall not be used for this vehicle C-ITS service.

Tested by:

#### 3.1.8 Network and transport layer

#### Requirement (i)

RS\_tcStVe\_135

The interface parameter destination area in IF.DEN.1 [ETSI EN 302 637-3] shall be equal to a circular shape with centre point equal to *eventPosition* and radius equal to *relevanceDistance*. Tested by:



#### 3.1.9 Security layer

#### Requirement (i)

RS\_tcStVe\_137

When the triggering conditions as described in clause 3.1.2 apply, the application shall request the blocking of the AT changeover as defined in RS\_BSP\_184.

Tested by:

## 3.2 Stationary vehicle warning - broken-down vehicle

#### 3.2.1 Description of vehicle C-ITS service

#### Other (informational)

RS\_tcStVe\_190

This clause describes the triggering of V2V messages for broken-down vehicle. Though various reasons could cause a vehicle breakdown, such as bursting tires, lack of fuel or engine failure, this clause focuses on reasons indicated by breakdown warning messages in the instrument cluster.

#### Other (informational)

RS\_tcStVe\_191

The following vehicle C-ITS services are related to this service, because they share similar triggering conditions:

- 'special vehicle warning stationary recovery service warning';
- 'stationary vehicle warning stopped vehicle';
- 'stationary vehicle warning post-crash'.

Requirement (i) RS\_tcStVe\_138

A DENM signal for 'Stationary vehicle warning - broken-down vehicle' C-ITS service shall be sent to the stack only if the conditions described in the clauses 3.2.2, 3.2.3 and 3.2.4 are evaluated as being met. If these conditions are not fulfilled, a DENM signal for this C-ITS service shall not be generated.

Note: A DENM signal prompts the stack to generate a new, update or cancellation DENM respectively.

Tested by:

#### 3.2.2 Triggering conditions

#### 3.2.2.1 Preconditions

#### Requirement (i)

RS\_tcStVe\_139

The following preconditions shall be satisfied when this use case is triggered:

1.) no breakdown warning message, that prevents the driver from continuing to drive, e.g. oil pressure, engine temperature, engine malfunction warning light or other comparable warning messages.

Note: This service is not required to check ignition terminal 15 status for triggering (can be on or off). Operation of this service is optional when ignition terminal 15 is off.

Tested by:



Requirement (i) RS\_tcStVe\_206

Parallel activation with the other related vehicle C-ITS services shall be avoided. Where the 'stopped vehicle' and/or 'post-crash' vehicle C-ITS services are triggered simultaneously, the vehicle C-ITS services shall be prioritised as follows:

- 1.) 'post-crash' (highest priority);
- 2.) 'broken-down vehicle';
- 3.) 'stopped vehicle' (lowest priority).

The higher priority service shall generate a new DENM and the overruled lower priority service shall not continue to generate update DENMs. An active repetition of the lower priority service may continue, a termination DENM for lower priority services should not be generated.

Tested by:

#### 3.2.2.2 Service-specific conditions

#### Requirement (i)

RS\_tcStVe\_140

If the precondition in RS\_tcStVe\_139 and all of the following conditions are satisfied, the triggering conditions for this vehicle C-ITS service are fulfilled and the generation of a DENM shall be triggered:

- the ego vehicle has enabled hazard lights;
- the vehicle is stationary;
- the *Triggering Timer* has expired.

Note: PTWs may not be equipped with hazard lights. PTW without hazard lights will not trigger this use case.

Tested by:

Requirement (i) RS\_tcStVe\_142

If the vehicle has enabled hazard lights and is stationary, the *Triggering Timer* shall be set to 30 s and started counting down.

The *Triggering Timer* shall be further reduced by 10 s for each of the following conditions that is fulfilled:

- a) the automatic transmission (AUT) is set to 'park' for at least 3 s;
- b) the gear box is set to idle for at least 3 s;
- c) the parking brake is enabled for at least 3 s:
- d) an arbitrary number of the seatbelt buckles change from 'connected' to 'disconnected' for at least 3 s;

The *Triggering Timer* shall be set to 0 s if at least one of the following conditions is fulfilled:

- e.1) an arbitrary number of doors are open for at least 3 s OR
- e.2) e.2) PTW>the side or main stand is used for at least 3 s
- f) the ignition terminal is switched from on to off for at least 3 s;
- g) the boot is open for at least 3 s;
- h) the bonnet is open for at least 3 s.

Tested by:

Requirement (i) RS\_tcStVe\_143



All above listed procedures for the timer reduction shall be applied only once during initial detection. If the *Triggering Timer* has been counted down to 0, no further reduction is necessary in the current detection cycle.

Tested by:

Requirement (i) RS tcStVe 144

During the runtime of the *Triggering Timer*, the hazard lights shall be enabled and the vehicle shall be stationary all the time. Otherwise the detection shall be cancelled.

Tested by:

#### 3.2.2.3 Information quality

#### Requirement (i)

RS tcStVe 145

The value of the data element *informationQuality* in the DENM depends on the current conditions from a) to h) of the requirement RS\_tcStVe\_142. The *informationQuality* value shall be set in accordance with the following table (highest possible value shall be used):

Table 5: Information quality of 'stationary vehicle - broken-down vehicle'

Event detection	Value of informationQuality
No TRCO-compliant implementation	unknown(0)
None of conditions a) — h) are fulfilled.	1
At least one condition of a) — d) is fulfilled.	2
At least one condition of e) — h) is fulfilled.	3

Note: an update of the information quality is performed as described in RS\_tcStVe\_146. Tested by:

#### 3.2.3 Termination conditions

#### Requirement (i)

RS\_tcStVe\_147

This vehicle C-ITS service is terminated by a cancellation of the originating vehicle C-ITS station. At the termination of the vehicle C-ITS service, update DENM request shall be terminated.

Tested by:

#### 3.2.3.1 Cancellation

#### Requirement (i)

RS\_tcStVe\_148

If at least one of the following conditions is satisfied before the period set in the data element *validityDuration* has expired, the generation of a cancellation DENM shall be triggered:

- a) the vehicle is no longer stationary for a duration of 5 s;
- b) the hazard lights are disabled;
- c) the position of the vehicle has changed more than 500 m (e.g. because the vehicle



has been towed away).

Note: The cancellation condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that cancellation condition.

Tested by:

#### 3.2.3.2 Negation

Requirement (i) RS\_tcStVe\_149

A negation DENM shall not be used for this vehicle C-ITS service.

Tested by:

#### **3.2.4 Update**

Requirement (i) RS\_tcStVe\_150

If the previously triggered DENM for a detected *Broken-down Vehicle* was not cancelled (see RS\_tcStVe\_148), the generation of an update DENM shall be triggered every 15 s.

Tested by:

Requirement (i) RS\_tcStVe\_151

In the update phase, only the triggering conditions shall be checked (timers shall not be evaluated further).

Tested by:

Requirement (i) RS tcStVe 152

If the ignition terminal 15 is switched from on to off, an update DENM shall be triggered immediately.

Tested by:

Requirement (i) RS\_tcStVe\_153

New values shall be assigned to data fields or elements in the DENM according to the changed event (e.g. *detectionTime* or *informationQuality*, see RS\_tcStVe\_157).

Note: The update condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that update condition.

Tested by:

Requirement (i) RS\_tcStVe\_146

If the triggering conditions change between two updates, the *informationQuality* shall not be changed until the next update. If the changed conditions are still fulfilled while the DENM is updated, the *informationQuality* shall be updated.

Tested by:



#### 3.2.5 Repetition duration and repetition interval

Requirement (i) RS\_tcStVe\_154

DENMs, that are new, have been updated or have been cancelled shall be repeated for a *repetitionDuration* of 15 s with a *repetitionInterval* of 1 s. Therefore, the interface parameters *Repetition duration* and *Repetition interval* between the application and the DEN basic service shall be set in accordance with the above values.

Tested by:

Requirement (i) RS\_tcStVe\_155

In the case of an enabled ignition terminal 15, the *validityDuration* shall be set to 30 s. Therefore, one can prevent a gap of DENMs if the *repetitionDuration* of the original DENM has expired and the update has not yet been received.

Note: The *validityDuration* is set to a higher value in the case of a disabled ignition terminal 15 than in the case of an enabled ignition terminal 15. This is due to the fact that update DENM cannot be triggered and can no longer be sent. Therefore, the last DENM shall be kept alive longer.

Note: Where two DENMs with the same *causeCode* originate from the same vehicle C-ITS station, the case shall be managed by the receiving C-ITS station.

Tested by:

#### 3.2.6 Traffic class

#### Requirement (i)

RS\_tcStVe\_156

New, update and cancellation DENMs shall be set to traffic class 1.

Tested by:

#### 3.2.7 Message parameters

#### 3.2.7.1 DENM

#### Requirement (i)

RS\_tcStVe\_157

The following table specifies the data elements of the DENM that shall be set.

Table 6: DENM data elements of 'stationary vehicle warning — broken-down vehicle'

Data field	Value			
	Management container			
actionID	Identifier of a DENM. Shall be set in accordance with [TS 102 89-2].			
detectionTime	Timestamplts-timestamp at which the event is detected by the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].  Shall be refreshed for an update DENM.			



referenceTime	Timestamplts-timestamp at which a new, update or cancellation DENM is generated. Shall be set in accordance with [TS 102 894-2].			
termination	Shall not be set in the case of a new or update DENM. Shall be set to isCancellation(0) in the case of a cancellation DENM.			
eventPosition	ReferencePosition. Shall be set in accordance with [TS 102 894-2].			
	Shall be refre	shed for an update DEN	IM.	
relevanceDistance	lessThan100	0m(4)		
	If the roadTyp	pe is known the value sh	nall be set as follows:	
	RoadType	Direction		
	0	allTrafficDirections(0)		
relevanceTrafficDirection	1	upstreamTraffic(1)		
	2	allTrafficDirections(0)		
	3	upstreamTraffic(1)		
	Otherwise, the value shall be set to allTrafficDirections(0)			
validityDuration	<ul> <li>Ignition terminal 15 enabled: 30 s</li> <li>Ignition terminal 15 disabled: 900 s</li> </ul>			
stationType	The type of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
	Situ	uation container		
informationQuality	See RS_tcStVe_145. Shall be refreshed for every update DENM.			
causeCode	stationaryVehicle(94)			
subCauseCode	vehicleBreakdown(2)			
	Loc	cation container		
eventSpeed	Speed of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
,	Shall be refreshed for an update DENM.			
eventPositionHeading	Heading of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
	Shall be refreshed for an update DENM.			
traces	PathHistory of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			



	If the PathDeltaTime is used in the PathPoints, the PathDeltaTime of the first PathPoint (closest point to the ReferencePosition) shall be refreshed for an update DENM. All other PathPoints shall not be refreshed. If the PathDeltaTime of the first PathPoint exceeds the maximum value in accordance with [TS 102 894-2], the PathDeltaTime shall not be further refreshed. If the PathDeltaTime is not used in the PathPoints, the PathHistory shall not be refreshed for an update DENM.					
	RoadType of is situated.	the road on which the do	etecting vehicle C-ITS station			
	Shall be refre	shed for an update DEN	NM.			
	Shall be set in the following	<del>-</del>	02 894-2] in combination with			
	Urban / non-urban	Structural separation	Data element			
	Urban	No	urban- NoStructuralSeparation ToOppositeLanes(0)			
_	Urban	Yes	urban- WithStructuralSeparation ToOppositeLanes(1)			
roadType	Urban	Unknown	urban- NoStructuralSeparation ToOppositeLanes(0)			
	Non-urban	No	nonUrban- NoStructuralSeparation ToOppositeLanes(2)			
	Non-urban	Yes	nonUrban- WithStructuralSeparation ToOppositeLanes(3)			
	Non-urban	Unknown	nonUrban- NoStructuralSeparation ToOppositeLanes(2)			
	If the information about the urban/non-urban status cannot be determined, the data element shall be omitted.					
	Alacarte container					
lanePosition	If the lanePosition is provided by an on-board sensor (e.g. radar, camera), the value shall be set in accordance with [TS 102 894-2]. Use of GNSS and a digital map to estimate the lane number is not legitimate for this version of the triggering condition.					
	If the lanePos	sition is unknown, the da	ata element shall be omitted.			
	Shall be refreshed for an update DENM.					
Ala	Alacarte container: StationaryVehicleContainer					



stationarySince

Shall be set according to the duration in minutes of the detecting vehicle C-ITS station being stationary. Shall be set in accordance with [TS 102 894-2].

Shall be refreshed for an update DENM.

Tested by:

#### 3.2.7.2 CAM

Requirement (i) RS tcStVe 158

CAM adaption shall not be used for this vehicle C-ITS service.

Tested by:

#### 3.2.8 Network and transport layer

Requirement (i) RS\_tcStVe\_159

The interface parameter destination area in IF.DEN.1 [ETSI EN 302 637-3] shall be equal to a circular shape with centre point equal to *eventPosition* and radius equal to *relevanceDistance*. Tested by:

#### 3.2.9 Security layer

## Requirement (i) RS\_tcStVe\_161

When the triggering conditions as described in clause 3.2.2 apply, the application shall request the blocking of the AT changeover as defined in RS\_BSP\_184.

Tested by:

# 3.3 Stationary vehicle warning - post-crash

#### 3.3.1 Description of vehicle C-ITS service

#### Other (informational)

RS\_tcStVe\_195

This clause describes the triggering conditions for a V2V DENM transmission caused by a traffic accident.

#### Other (informational)

RS\_tcStVe\_196

The following vehicle C-ITS services are related to this service, because they share similar triggering conditions:

- 'stationary vehicle warning stopped vehicle';
- 'stationary vehicle warning broken-down vehicle'.

#### Requirement (i)

A DENM signal for 'Stationary vehicle warning - post-crash' C-ITS service shall be sent to the stack only if the conditions described in the clauses 3.3.2, 3.3.3 and 3.3.4 are evaluated as being met. If these conditions are not fulfilled, a DENM signal for this C-ITS service shall not

RS\_tcStVe\_162



be generated.

Note: A DENM signal prompts the stack to generate a new, update or cancellation DENM respectively.

Tested by:

#### 3.3.2 Triggering conditions

#### 3.3.2.1 Preconditions

Requirement (i)

RS tcStVe 163

No specific preconditions apply for this vehicle C-ITS service.

Tested by:

Requirement (i) RS\_tcStVe\_207

Parallel activation with the other related vehicle C-ITS services shall be avoided. Where the vehicle C-ITS services 'stopped vehicle' and/or 'broken-down vehicle' are triggered simultaneously, the vehicle C-ITS services shall be prioritised as follows:

- 1.) 'post-crash' (highest priority);
- 2.) 'broken-down vehicle';
- 3.) 'stopped vehicle' (lowest priority).

The higher priority service shall generate a new DENM and the overruled lower priority service shall not continue to generate update DENMs. An active repetition of the lower priority service may continue, a termination DENM for lower priority services should not be generated.

Tested by:

#### 3.3.2.2 Service-specific conditions

#### Requirement (i)

RS tcStVe 164

If the preconditions in RS\_tcStVe\_163 and at least one of the following conditions are satisfied, the triggering conditions for this vehicle C-ITS service are fulfilled and the generation of a DENM shall be triggered:

- a) an eCall has been triggered manually by an occupant of the vehicle by the eCall button and the vehicle becomes stationary within 15 s. If the vehicle is already stationary, the condition is fulfilled immediately;
- b) a low-severity crash is detected without the activation of an irreversible occupant restraint system (e.g. high-voltage battery cut-off, door unlock) and the vehicle becomes stationary within 15 s. If the vehicle is already stationary, the condition is fulfilled immediately;
- c) a pedestrian collision is detected with the activation of at least one irreversible pedestrian-protection system (e.g. pop-up bonnet, outside airbag) and the vehicle becomes stationary within 15 s. If the vehicle is already stationary, the condition is fulfilled immediately;
- d) a high-severity crash is detected with the activation of at least one irreversible occupant-restraint system (e.g. pyrotechnic belt-tightener, airbag).

Note: The condition 'vehicle becomes/is stationary' is defined in RS\_tcStVe\_208.



Note: The conditions need to be checked only if the necessary power supply is present. This means that crash-secure implementation of the system is not required.

Tested by:

#### 3.3.2.3 Information quality

#### Requirement (i)

RS\_tcStVe\_166

The value of the data element *informationQuality* in the DENM depends on the current conditions from a) to d) of the requirement RS\_tcStVe\_164. The *informationQuality* value shall be set in accordance with the following table (highest possible value shall be used):

Table 7: Information quality of 'stationary vehicle — post-crash'

Event detection	Value of InformationQuality
No TRCO-compliant implementation	unknown(0)
Condition a) is fulfilled.	1
Condition b) or c) is fulfilled.	2
Condition d) is fulfilled.	3

Note: an update of the information quality is performed as described in RS\_tcStVe\_167. Tested by:

#### 3.3.3 Termination conditions

#### Requirement (i)

RS\_tcStVe\_168

This vehicle C-ITS service is terminated by a cancellation of the originating vehicle C-ITS station. At the termination of the vehicle C-ITS service, update DENM request shall be terminated.

Tested by:

#### 3.3.3.1 Cancellation

#### Requirement (i)

RS\_tcStVe\_169

Once at least one of the following conditions is satisfied before the period set in the data element *validityDuration* has expired, the generation of a cancellation DENM shall be triggered:

- a) the ego vehicle is not stationary for a duration of 15 s;
- b) the position of the vehicle has changed more than 500 m (e.g. because the vehicle has been towed away).

Note: The cancellation condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that cancellation condition.

Tested by:



#### 3.3.3.2 Negation

#### Requirement (i)

RS tcStVe 170

A negation DENM shall not be used for this vehicle C-ITS service.

Tested by:

#### **3.3.4** Update

Requirement (i)

RS tcStVe 171

An update DENM shall be triggered every 60 s if the vehicle C-ITS service has not been cancelled.

Tested by:

Requirement (i)

RS\_tcStVe\_172

If the ignition terminal 15 is switched from on to off, an update DENM shall be triggered immediately.

Tested by:

Requirement (i)

RS tcStVe 173

New values shall be assigned to data fields or elements in the DENM according to the changed event (e.g. *detectionTime* or *informationQuality*, see RS tcStVe 177).

Note: The update condition does not imply that the vehicle C-ITS station needs to be permanently operational or extend its operation during that update condition.

Tested by:

Requirement (i)

RS\_tcStVe\_167

If the triggering conditions change between two updates, the *informationQuality* shall not be changed until the next update. If the changed conditions are still fulfilled while the DENM is updated, the *informationQuality* shall be updated.

Tested by:

#### 3.3.5 Repetition duration and repetition interval

#### Requirement (i)

RS\_tcStVe\_174

DENMs, that are new, have been updated or have been cancelled, shall be repeated for a *repetitionDuration* of 60 s with a *repetitionInterval* of 1 s. Therefore, the interface parameters *Repetition duration* and *Repetition interval* between the application and the DEN basic service shall be set in accordance with the above values.

Tested by:

Requirement (i)

RS\_tcStVe\_175

In the case of an enabled ignition terminal 15, the *validityDuration* shall be set to 180 s. Therefore, one can prevent a gap of DENMs if the *repetitionDuration* of the original DENM has expired and the update has not yet been received.



Note: The *validityDuration* is set to a higher value in the case of a disabled ignition terminal 15 than in the case of an enabled ignition terminal 15. This is due to the fact that update DENM cannot be triggered and can no longer be sent. Therefore, the last DENM shall be kept alive longer.

Note: Where two DENMs with the same *causeCode* originate from the same vehicle C-ITS station, the case shall be managed by the receiving C-ITS station.

Tested by:

#### 3.3.6 Traffic class

#### Requirement (i) RS\_tcStVe\_176

New, update and cancellation DENMs shall be set to traffic class 1.

Tested by:

#### 3.3.7 Message parameters

#### 3.3.7.1 **DENM**

Requirement (i) RS\_tcStVe\_177

The following table specifies the data elements of the DENM that shall be set.

Table 8: DENM data elements of 'stationary vehicle warning — post-crash'

Data field	Value			
Management container				
actionID	Identifier of a DENM. Shall be set in accordance with [TS 102 894-2].			
detectionTime	TimestampIts-timestamp at which the event is detected by to originating vehicle C-ITS station. Shall be set in accordance w [TS 102 894-2].			
	Shall be refreshed for an update DENM.			
referenceTime	Timestamplts-timestamp at which a new DENM, an update DENM or a cancellation DENM is generated. Shall be set in accordance with [TS 102 894-2].			
termination	Shall not be set in case of new or update DENM. Shall be set to isCancellation(0) in case of a cancellation DENM.			
eventPosition	ReferencePosition. Shall be set in accordance with [TS 102 894-2].			
	Shall be refreshed for an update DENM.			
relevanceDistance	lessThan5km(5)			
relevanceTrafficDirection	If the roadType is known the value shall be set as follows:			
	RoadType	Direction		



	0	allTrafficDirections(0)		
	1	upstreamTraffic(1)		
	2	allTrafficDirections(0)		
	3	upstreamTraffic(1)		
	Otherwise, the value shall be set to allTrafficDirections(0)			
validityDuration	<ul> <li>Ignition terminal 15 enabled: 180 s</li> <li>Ignition terminal 15 disabled: 1 800 s</li> </ul>			
stationType	The type of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
	Situ	uation container		
informationQuality	See RS_tcSt	See RS_tcStVe_166. Shall be refreshed for every update DENM.		
causeCode	stationaryVel	nicle(94)		
subCauseCode	postCrash(3)			
	Loc	cation container		
eventSpeed	Speed of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
·	Shall be refre	shed for an update DEN	IM.	
eventPositionHeading	Heading of the originating vehicle C-ITS station. Shall be set in accordance with [TS 102 894-2].			
-	Shall be refreshed for an update DENM.			
	PathHistory of the originating vehicle C-ITS station. Shall be set accordance with [TS 102 894-2].			
traces	If the PathDeltaTime is used in the PathPoints, the PathDeltaTime of the first PathPoint (closest point to the ReferencePosition) shall be refreshed for an update DENM. All other PathPoints shall not be refreshed. If the PathDeltaTime of the first PathPoint exceeds the maximum value in accordance with [TS 102 894-2], the PathDeltaTime shall not be further refreshed. If the PathDeltaTime is not used in the PathPoints, the PathHistory shall not be refreshed for an update DENM.			
	RoadType of is situated.	the road on which the de	etecting vehicle C-ITS station	
	Shall be refreshed for an update DENM.			
roadType	Shall be set in accordance with [TS 102 894-2] in combination with the following rules:			
rodurypo	Urban / non-urban	Structural separation	Data element	
	Urban	No	urban- NoStructuralSeparation ToOppositeLanes(0)	



1			1	
	Urban	Yes	urban- WithStructuralSeparation ToOppositeLanes(1)	
	Urban	Unknown	urban- NoStructuralSeparation ToOppositeLanes(0)	
	Non-urban	No	nonUrban- NoStructuralSeparation ToOppositeLanes(2)	
	Non-urban	Yes	nonUrban- WithStructuralSeparation ToOppositeLanes(3)	
	Non-urban	Unknown	nonUrban- NoStructuralSeparation ToOppositeLanes(2)	
If the information about the urban/non-urban status cannot be determined, the data element shall be omitted.				
Alacarte container				
If the lanePosition is provided by an on-board sensor (e.g. radar, camera), the value shall be set in accordance with [TS 102 894-2].  Use of GNSS and a digital map to estimate the lane number is not lanePosition				
	If the lanePosition is unknown, the data element shall be o			
	Shall be refreshed for an update DENM.			
Alacarte container: StationaryVehicleContainer				
stationarySince	Shall be set according to the duration in minutes of the detecting vehicle C-ITS station being stationary. Shall be set in accordance with [TS 102 894-2].			
Shall be refreshed for an update DENM.			NM.	

Tested by:

#### 3.3.7.2 CAM

Requirement (i) RS\_tcStVe\_178

CAM adaption shall not be used for this vehicle C-ITS service.

Tested by:

#### 3.3.8 Network and transport layer

## Requirement (i)

The interface parameter destination area in IF.DEN.1 [ETSI EN 302 637-3] shall be equal to a circular shape with centre point equal to *eventPosition* and radius equal to *relevanceDistance*.

Tested by:

RS\_tcStVe\_179



## 3.3.9 Security layer

#### Requirement (i)

RS\_tcStVe\_181

When the triggering conditions as described in clause 3.3.2 apply, the application shall request the blocking of the AT changeover as defined in RS\_BSP\_184.

Tested by: